



PANORAMICA | ALIMENTATORI FLUO

Alimentatori							Lampada					
Cod. ord.	Tipo	Tensione AC V, Hz	Sezione mm	a/l mm	b/l1 mm	c/l2 mm	Tipo	Potenza W	EEI	CE	Disponibile su richiesta	Alternativa
163683	L 4/6/8.304	230, 50	28x41	85	75	34	T5 (T16)	4	B2	—	X	
								2x4	B1	—	X	
								6	B1	—	X	
								8	B1	—	X	
163694	L 7/9/11.307	230, 50	28x41	85	75	34	TC-S	5	B2	—	X	
								7	B2	—	X	
								9	B1	—	X	
								11	B1	—	X	
163711	LN 13.313	230, 50	28x41	85	75	34	T5 (T16)	13	B1	—	✓	
								2x6	B1	—	✓	
								2x8	B1	—	✓	
								TC-D	10	B2	—	✓
								TC-D/TC-T	13	B2	—	✓
								TC-S	2x5	B2	—	X
								2x7	B2	—	X	
								2x9	B2	—	✓	
								TC-DD	10	B2	—	✓
								TC-DD	16	B1	—	✓
163730	LN 16.316	230, 50	28x41	85	75	34	T8 (T26)	16	B1	—	✓	
							TC-DD	16	B1	—	✓	
163763	LN 18I.319	230, 50	28x41	85	75	34	TC-D/TC-T	18	B1	—	✓	
163861	LN 15.329	230, 50	28x41	150	140	60	T8 (T26)	15	B2	—	✓	
164013	L 25.346	230, 50	28x41	150	140	60	T12 (T38)	25	B1	—	✓	
164033	L 30.347	230, 50	28x41	150	140	60	T8 (T26)	2x15	—	—	✓	
164572	LN 18.510	230, 50	28x41	155	140	92	T8 (T26)	14	B2	—	✓	560657
								T8 (T26)/T12 (T38)	18/20	B1	—	✓
								TC-F/TC-L	18	B1	—	✓
								TC-DD	28	B1	—	✓
164590	LN 36.511	230, 50	28x41	155	140	92	T8 (T26)	38	B1	—	✓	560659, 560664
								T8 (T26)/T12 (T38)	36/40	B1	—	✓
								TC-F/TC-L	36	B1	—	✓
164680	LN 30.530	230, 50	28x41	155	140	92	T-R	22	B2	—	✓	
169389	LN 58.568	230, 50	28x41	233	220	160	T8 (T26)/T12 (T38)	58/65	B1	—	✓	560661, 560665
								T-U	58	B1	—	✓
169645	LN 30.801	230, 50	28x41	150	140	60	T8 (T26)	2x15	B2	—	✓	
								30	B2	—	✓	
169779	LN 36.570	230, 50	28x41	155	140	92	T8 (T26)	38	B1	—	✓	560659, 560664
								T8 (T26)/T12 (T38)	36/40	B1	—	✓
								TC-F/TC-L	36	B1	—	✓
								TC-DD	38	B1	—	✓
								T-U/TR	36/40	B1	—	✓
								T-R	32	B2	—	✓
508186	LN 58.116	230, 50	28x41	190	180	92	T8 (T26)/T12 (T38)	58/65	B2	—	✓	560661, 560665
								T-U	58	B2	—	✓
508922	LN 18I.940	230, 50	28x41	85	75	34	TC-D/TC-T	18	B1	—	✓	
509349	LN 58.990	230, 50	28x41	190	180	110	T8 (T26)/T12 (T38)	58/65	B2	—	✓	560661, 560665
509502	LN 26.813	230, 50	28x41	110	100	45	TC-D/TC-T	26	B2	—	✓	
527191	LN 36.130	230, 50	28x41	150	140	60	T8 (T26)/T12 (T38)	36/40	B2	—	✓	560659, 560664
529029	LN 36.149	230, 50	28x41	150	140	60	T8 (T26)	38	B2	—	✓	560659, 560664
								T8 (T26)/T12 (T38)	36/40	B2	—	✓
								TC-F/TC-L	36	B2	—	✓

PANORAMICA | ALIMENTATORI FLUO

Alimentatori							Lampada					
Cod. ord.	Tipo	Tensione AC V, Hz	Sezione mm	a/L mm	b/L1 mm	c/L2 mm	Tipo	Potenza W	EEI	CE	Disponibile su richiesta	Alternativa
529029	LN 36.149	230, 50	28x41	150	140	60	TC-DD	38	B2	—	✓	560659, 560664
530941	LN 18.131	230, 50	28x41	150	140	60	TU/TR	36/40	B2	—	✓	560657
							TC-D/TC-T	26	B1	—	✓	
							TC-F/TC-L	18	B2	—	✓	
							TC-DD	28	B1	—	✓	
							TU	18	B2	—	✓	
532155	LN 2x18.135	230, 50	28x41	150	140	45	T8 (T26)/T12 (T38)	2x18/20	B1	—	✓	
534490	LN 24/26.804	230, 50	28x41	150	140	60	TC-F/TC-L	2x18	B1	—	✓	560657
							TC-F/TC-L	24	B2	—	✓	
							TC-DD	24	B2	—	✓	
							TU	18	B2	—	✓	
							T8 (T26)	38	—	—	✓	
535977	LN 36.132	230, 50	28x41	150	140	45	T8 (T26)/T12 (T38)	36/40	—	—	✓	560659, 560664
							TC-F/TC-L	36	—	—	✓	
							TC-DD	38	—	—	✓	
							TU/TR	36/40	—	—	✓	
538072	L 36l.342	230, 50	28x41	195	180	110	T8 (T26)	36-1	B2	—	✓	
560657	LN 18.645	230, 50	53x66	145	120	75	T8 (T26)/T12 (T38)	18/20	A2	CE		
560659	LN 36.646	230, 50	53x66	108	86	36	T8 (T26)/T12 (T38)	2x18/20	A2	CE		
560661	LN 58.647	230, 50	53x66	108	86	36	T8 (T26)/T12 (T38)	36/40	A2	CE		
							TC-F/TC-L	36	—	—	✓	
							TC-DD	38	—	—	✓	
							TU/TR	36/40	—	—	✓	
							T8 (T26)	38	—	—	✓	
560664	LN 36.648	230, 50	28x41	232,5	220	160	T8 (T26)/T12 (T38)	2x18/20	A2	CE		
560665	LN 58TD.649*	230, 50	28x41	232,5	220	160	T8 (T26)/T12 (T38)	36/40	A2	CE		
							TC-F/TC-L	38	A2	CE		
							TC-DD	38	A2	CE		
							TU/TR	36/40	A2	CE		
							T8 (T26)	38	A2	CE		
164326	L 4/6/8.404	240, 50	28x41	85	75	34	T5 (T16)	4	B2	—	✗	
164335	L 7/9/11.411	240, 50	28x41	85	75	34	T5 (T16)	2x4	B1	—	✗	
							6	B1	—	—	✗	
							8	B1	—	—	✗	
							5	B2	—	—	✗	
							7	B2	—	—	✗	
164342	LN 13.413	240, 50	28x41	85	75	34	T5 (T16)	9	B1	—	✓	
164342	LN 13.413	240, 50	28x41	85	75	34	T5 (T16)	11	B1	—	✓	
							13	B1	—	—	✓	
							2x6	B1	—	—	✓	
							2x8	B1	—	—	✓	
							TC-D	10	B2	—	✓	
164342	LN 13.413	240, 50	28x41	85	75	34	TC-D/TC-T	13	B1	—	✓	
164343	LN 13.413	240, 50	28x41	85	75	34	TC-S	2x5	B2	—	✓	
							2x7	B2	—	—	✓	
							2x9	B2	—	—	✓	
							TC-DD	10	B2	—	✓	
							TU/TR	18	B1	—	✓	
164353	LN 18l.418	240, 50	28x41	85	75	34	TC-D/TC-T	16	B1	—	✓	
164358	LN 16.417	240, 50	28x41	85	75	34	T5 (T26)	16	B1	—	✓	
164438	L 36/40.443	240, 50	28x41	150	140	60	T8 (T26)	38	—	—	✓	

* TD = Semialimentatore (sono necessari due alimentatori per una lampada)



PANORAMICA | ALIMENTATORI FLUO

Alimentatori							Lampada					
Cod. ord.	Tipo	Tensione AC V, Hz	Sezione mm	a/l mm	b/l1 mm	c/l2 mm	Tipo	Potenza W	EEI	CE	Disponibile su richiesta	Alternativa
164438	L 36/40.443	240, 50	28x41	150	140	60	T8 (T26)/T12 (T38)	36/40	—	—	✓	
							TC-F/TC-L	36	—	—	✓	
							TC-DD	38	—	—	✓	
							T-U/TR	36/40	—	—	✓	
164555	LN 36.505	240, 50	28x41	155	140	92	T8 (T26)	38	B1	—	✓	
							T8 (T26)/T12 (T38)	2x18/20	B1	—	✓	
								36/40	B1	—	✓	
							TC-F/TC-L	2x18	B1	—	✓	
								36	B1	—	✓	
							TR	32	B1	—	✓	
							T-U/TR	36/40	B1	—	✓	
164560	LN 58.506	240, 50	28x41	233	220	160	T8 (T26)/T12 (T38)	58/65	B1	—	✓	
							T-U	58	B1	—	✓	
164566	LN 18.507	240, 50	28x41	155	140	92	T8 (T26)/T12 (T38)	18/20	B1	—	✓	
							TC-F/TC-L	18	B1	—	✓	
								24	B1	—	✓	
							T-U	18	B1	—	✓	
507936	LN 58.192	240, 50	28x41	190	180	110	T8 (T26)/T12 (T38)	58/65	B2	—	✓	
							T-U	58	B2	—	✓	
527196	LN 36.201	240, 50	28x41	150	140	60	T8 (T26)	38	B2	—	✓	
							T8 (T26)/T12 (T38)	2x18/20	B1	—	✓	
								36/40	B2	—	✓	
							TC-F/TC-L	2x18	B1	—	✓	
								36	B2	—	✓	
							TC-DD	38	B2	—	✓	
							T-U/TR	36/40	B2	—	✓	
533043	LN 18.162	240, 50	28x41	150	140	60	T8 (T26)/T12 (T38)	18/20	B2	—	✓	
							TC-D/TC-T	26	B1	—	✓	
							TC-F/TC-L	18	B2	—	✓	
								24	B2	—	✓	
							TC-DD	28	B1	—	✓	
533067	LN 30.806	240, 50	28x41	150	140	60	T8 (T26)	2x15	B2	—	✓	
								30	B2	—	✓	
							T-U	18	B2	—	✓	
533650	LN 75.170	240, 50	28x41	190	180	110	T8 (T26)/T12 (T38)	70/75	B2	—	✓	
534252	LN 58.722	240, 50	28x41	190	180	92	T8 (T26)/T12 (T38)	58/65	B2	—	✓	
							T-U	58	B2	—	✓	
534627	L 18.936	240, 50	28x41	150	140	45	T8 (T26)/T12 (T38)	18/20	—	—	✓	
							TC-F/TC-L	18	—	—	✓	
								24	—	—	✓	
							TC-DD	28	—	—	✓	
							T-U	18	—	—	✓	
535778	LN 2x18.135	240, 50	28x41	150	140	45	T8 (T26)/T12 (T38)	2x18/20	B1	—	✓	
							TC-F/TC-L	2x18	B1	—	✓	
545405	LN 26.238	240, 50	28x41	105	95	45	TC-D/TC-T	26	B2	—	✓	
547145	LN 21.293	240, 50	28x41	105	95	45	TC-DD	21	B1	—	✓	
164828	L 58.625	220, 50	28x41	190	180	92	T8 (T26)/T12 (T38)	58/65	—	—	✓	
							T-U	58	—	—	✓	
530252	L 36.158	220, 50	28x41	150	140	45	T8 (T26)	38	—	—	✓	
							T8 (T26)/T12 (T38)	2x18/20	—	—	✓	
								36/40	—	—	✓	
							TC-F/TC-L	2x18	—	—	✓	



PANORAMICA | ALIMENTATORI FLUO

Alimentatori							Lampada						
Cod. ord.	Tipo	Tensione AC V, Hz	Sezione mm	a/l mm	b/l1 mm	c/l2 mm	Tipo	Potenza W	EEI	CE	Disponibile su richiesta	Alternativa	
530252	L 36.158	220, 50	28x41	150	140	45	TC-F/TC-L	36	—	—	✓		
							TC-DD	38	—	—	✓		
							T-U/TR	36/40	—	—	✓		
534624	L 18.933	220, 50	28x41	150	140	45	T8 (T26)/T12 (T38)	18/20	—	—	✓		
							TC-D/TC-T	26	—	—	✓		
							TC-F/TC-L	18	—	—	✓		
							24	—	—	—	✓		
							TC-DD	28	—	—	✓		
							T-U	18	—	—	✓		
163305	L 7/9/11.207	220, 60	28x41	85	75	34	TC-S	5	—	—	X		
								7	—	—	X		
								9	—	—	✓		
								11	—	—	✓		
164779	L 18I.602	220, 60	28x41	85	75	34	TC-D/TC-T	18	—	—	✓		
164870	L 58.657	220, 60	28x41	195	180	92	T8 (T26)/T12 (T38)	58/65	—	—	✓		
							T-U	58	—	—	✓		
509373	L 36.120	220, 60	28x41	150	140	45	T8 (T26)	38	—	—	✓		
							T8 (T26)/T12 (T38)	2x18/20	—	—	✓		
							36/40	—	—	—	✓		
							TC-F/TC-L	2x18	—	—	✓		
							36	—	—	—	✓		
							TC-DD	38	—	—	✓		
							T-U/TR	36/40	—	—	✓		
							T5 (T16)	2x6	—	—	✓		
520992	L 13.210	220, 60	28x41	85	75	34	T5 (T16)	2x8	—	—	✓		
								13	—	—	✓		
								TC-D	10	—	—	✓	
								TC-D/TC-T	13	—	—	✓	
								TC-S	2x5	—	—	✓	
								2x7	—	—	—	✓	
528582	L 18.121	220, 60	28x41	150	140	45	T8 (T26)/T12 (T38)	2x9	—	—	—	✓	
								TC-DD	10	—	—	✓	
								T-U	18	—	—	✓	
								T8 (T26)/T12 (T38)	18/20	—	—	✓	
								TC-D/TC-T	26	—	—	✓	
532149	L 18.121	220, 60	28x41	110	100	45	T8 (T26)/T12 (T38)	18	—	—	✓		
								18	—	—	✓		
								24	—	—	✓		
								T-U	18	—	—	✓	
								TC-DD	28	—	—	✓	
532644	L 4/6/8.218	220, 60	28x41	85	75	34	T5 (T16)	18	—	—	X		
								2x4	—	—	X		
								6	—	—	X		
								8	—	—	X		
537744	L 15.007	220, 60	28x41	150	140	45	T8 (T26)	15	—	—	✓		
537750	L 30.006	220, 60	28x41	150	140	45	T8 (T26)	2x15	—	—	✓		
								30	—	—	✓		
538801	L 18.149	220, 60	28x41	150	140	34	T8 (T26)/T12 (T38)	18/20	—	—	✓		
							TC-D/TC-T	26	—	—	✓		



PANORAMICA | ALIMENTATORI FLUO

Alimentatori							Lampada					
Cod. ord.	Tipo	Tensione AC V, Hz	Sezione mm	a/l mm	b/l1 mm	c/l2 mm	Tipo	Potenza W	EEI	CE	Disponibile su richiesta	Alternativa
538801	L 18.149	220, 60	28x41	150	140	34	TC-F/TC-L	18	—	—	✓	
								24	—	—	✓	
							TC-DD	28	—	—	✓	
538801	L 18.249	220, 60	28x41	150	140	34	TU	18	—	—	✓	
163318	L7/9.209	120, 60	28x41	85	75	34	TC-S	5	—	—	X	
								7	—	—	X	
								9	—	—	X	
170117	L 14.139	120, 60	28x41	85	75	34	T8 (T26)	14	—	—	X	