

LED LIGHT PANEL SMD

TRIPLE POWER EMITTER XP



TRIPLE POWER EMITTER XP

WU-M-422

Thanks to the use of highly efficient LEDs, TriplePowerEmitter modules guarantee an extremely high lumen output of up to 622 lm at max. 700 mA.

The modules can be safely operated with various constant current drivers (350 mA, 500 mA or 700 mA). Sufficient cooling must be ensured.

The TriplePowerEmitter modules are available in white, neutral white and warm white.

The modules are available without an optical attachment or with a fixed 10°, 15°, 20° or 40° optical attachment to enable the creation of different lighting scenes.

Typical Applications

- Integration in luminaires
- Architectural illumination
- Marking of paths, stairs, etc.
- Furniture lighting
- Light advertising
- Entertainment, shop design

TriplePowerEmitter XP

- **LONG SERVICE LIFETIME**
due to optimal thermal management
- **VERY HIGH LUMEN OUTPUT**
highly efficient (up to 108 lm/W)
- **AVAILABLE IN DIFFERENT CCTS**
white, neutral white and warm white
- **ATTACHMENT FOR LENSES WITH DIFFERENT BEAM ANGLES**
- **RESISTANT AGAINST SHOCK AND VIBRATIONS**

TriplePowerEmitter XP

Technical Notes

- PCB diameter: 45 mm
- Al-PCB for optimum thermal management
- ESD protection class 2



Electrical Characteristics

at ambient temperature $t_a = 25\text{ }^\circ\text{C}$

Type	Ref. No.	Voltage DC (V)						Power consumption (W)					
		350 mA		500 mA		700 mA		350 mA		500 mA		700 mA	
		typ.	max.	typ.	max.	typ.	max.	typ.	max.	typ.	max.	typ.	max.
All types	All types	9.6	11.7	9.9	12	10.2	12.3	3.36	4.1	4.95	6	7.14	8.61

Use of external LED constant current driver with max. 700 mA required.

Maximum Ratings

Exceeding the maximum ratings can lead to reduction of service life or destruction of the module.

Typ	Max. Operation current mA	Operation temperature range at tc-point		Storage temperature range		Reverse voltage V
		$^\circ\text{C min.}$	$^\circ\text{C max.}$	$^\circ\text{C min.}$	$^\circ\text{C max.}$	
All types	700	-20	+85	-20	+85	5

Optical Characteristics

at junction temperature $t_j = 25\text{ }^\circ\text{C}$

Type	Ref. No.	Colour	Correlated colour temperature K	Luminous flux (lm) at						CRI R_a	Beam angle $^\circ$
				350 mA		500 mA		700 mA			
				min.	typ.	min.	typ.	min.	typ.		
TriplePowerEmitter XP											
WU-M-422-XPE-CVW	546729	white	5650...6950	321	366	417	476	546	622	75	115
WU-M-422-XPE-NW	546727	neutral white	3700...4260	219	321	366	417	479	546	75	115
WU-M-422-XPE-WW	546733	warm white	2870...3200	242	282	314	366	411	479	80	115
TriplePowerEmitter XP 10°											
WU-M-422-XPE-CVW-10°	546735	white	5650...6950	289	329	376	428	491	560	75	10
WU-M-422-XPE-NW-10°	546736	neutral white	3700...4260	254	289	330	376	431	491	75	10
WU-M-422-XPE-WW-10°	546741	warm white	2870...3200	218	254	283	330	370	431	80	10
TriplePowerEmitter XP 20°											
WU-M-422-XPE-CVW-20°	546748	white	5650...6950	289	329	376	428	491	560	75	20
WU-M-422-XPE-NW-20°	546750	neutral white	3700...4260	254	289	330	376	431	491	75	20
WU-M-422-XPE-WW-20°	546749	warm white	2870...3200	218	254	283	330	370	431	80	20
TriplePowerEmitter XP 30°											
WU-M-422-XPE-CVW-30°	548088	white	5650...6950	289	329	376	428	491	560	75	30
WU-M-422-XPE-NW-30°	548089	neutral white	3700...4260	254	289	330	376	431	491	75	30
WU-M-422-XPE-WW-30°	548090	warm white	2870...3200	218	254	283	330	370	431	80	30
TriplePowerEmitter XP 40°											
WU-M-422-XPE-CVW-40°	546755	white	5650...6950	289	329	376	428	491	560	75	40
WU-M-422-XPE-NW-40°	546756	neutral white	3700...4260	254	289	330	376	431	491	75	40
WU-M-422-XPE-WW-40°	546757	warm white	2870...3200	218	254	283	330	370	431	80	40

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.

TriplePowerEmitter XP


Operating Life

50,000 hrs. (lumen maintenance L70/B10)

I _F 350 mA	I _F 500 mA	I _F 700 mA
t _c 75 °C	t _c 65 °C	t _c 55 °C

These values do not refer to the colour temperature.

Light Distribution Curves




Attachment optics with various radiation characteristics are available at Vossloh-Schwabe. Please find further information at www.vossloh-schwabe.com.

Mechanical Dimensions

Pre-assembled lead connection on request.

■ WU-M-422 WITHOUT OPTICS



Thermal Characteristics

Type	Thermal resistance, p-n-junction to t _c point (K/W)	Thermal resistance, p-n-junction to bottom of PCB (K/W)
All types		4.2


VS recommends an additional cooling element for improved thermal management.

Bins


The standard shipping format regarding the reference numbers on page 2 includes all chromaticity coordinate groups.

The concrete delivered group is marked on each product.

Reduction of orderable groups is possible only project-based.



■ WU-M-422 WITH OPTICS



The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.

TriplePowerEmitter XP

Assembly and Safety Information

Installation must be carried out under observation of the relevant regulations and standards. The LED modules are designed for operation within a casing or luminaire. Installation must be carried out in a voltage-free state (i.e. disconnection from the mains). The following advice must be observed; non-observance can result in the destruction of the LED assembly modules, fire and/or other hazards.

- ESD (electrostatic discharge) protection measures must be observed when handling and installing the LED modules. See VS's application notes on ESD protection.
- LED assembly modules must not be subjected to any undue mechanical stress, e. g.:
 - do not treat as bulk cargo
 - avoid shear and compressive forces during handling and installation
 - do not damage circuit paths
- LED assembly modules are designed for attachment using a thermally conductive adhesive, an adhesive foil (Ref. No. 536977) or M3 screws. Please observe the manufacturer's technical data provided at www.3M.com/converter. Products equipped with adhesive transfer tape must only be applied to dry and clean surfaces that are free from grease, oil, silicone or other soiling. It is therefore recommended to clean the substrate with isopropyl alcohol (IPA). Please ensure a full-surface bond over the entire contact area when sticking the module to the substrate. The following substances are regarded as critical for creating an adhesive bond:
 - Polyefins (polyethylene, polypropylene)
 - Rubber
 - Powder-coated materials
 - Silicone rubber
 - Teflon
- Owing to the varying application options and different types of surface as well as ambient conditions, VS accepts no liability for the quality of the adhesive bond achieved when mounting these products. Prior to sticking a VS product, care must be taken to check whether the material in question is actually suitable for the intended purpose under consideration of all possible application-relevant influences. Supplementary holders must be used if necessary. If opting for screw attachment, plastic screws or suitably insulated, non-loosening metal screws must be used.
- Safe operation only possible by the use of external constant current sources (I_{max} see table "Electrical Characteristics").
- Operation only with power supply units that feature the following protection:
 - Short-circuit protection
 - Overload protection
 - Overheating protection
 - SELV equiv. (Safety Extra Low Voltage)
- Please ensure the correct polarity of the leads prior to commissioning. Reversed polarity can destroy the modules.
- For optimal load of used constant current driver the modules can only be connected in series. The quantity of LED modules is limited by the sum of forward voltage and the capacity of used constant current driver. Safety regulations acc. to EN 60598 has to be observed if the sum of forward voltage exceed the permitted touchable value.
- A parallel connection of the modules is not allowed.
- Due to the manufacturing process, the PCBs of the LED assembly modules can have sharp edges and corners. Care must therefore be taken during handling and installation to avoid injury.
- To ensure problem-free operation, the specified maximum temperature at the tc point (see "Operating Life") must be observed (measured in accordance with EN 60598-1). To satisfy this point, it may be necessary to put measures in place to ensure any heat is dissipated from the PCB to the environment.
- In the event of outdoor applications or applications in damp locations, care must be taken to protect LED assembly modules against humidity, splashes and jets of water. Any corrosion damage resulting from humidity or contact with condensation will not be recognised as a defect or manufacturing fault. LED assembly modules are not specially protected against foreign bodies or dust. Depending on the type of application, further protection must be ensured to prevent dust and foreign bodies from entering.
- Tests have shown the following chemicals to be harmful to LEDs used on the modules. It is recommended not to use these chemicals anywhere in an LED system. The fumes from even small amounts of these chemicals may damage the LEDs.
 - Chemicals that might outgas aromatic hydrocarbons (e.g., toluene, benzene, xylene)
 - Methyl acetate or ethyl acetate (i.e., nail polish remover)
 - Cyanoacrylates (i.e., "Superglue")
 - Glycol ethers (including Radio Shack®, Precision Electronics Cleaner – dipropylene glycol monomethyl ether)
 - Formaldehyde or butadiene (including Ashland PLIOBOND® adhesive)
 - Dymax 984-LVUF conformal coating
 - Loctite Sumo glue
 - Gorilla glue
 - Clorox bleach
 - Clorox Clean-Up cleaner spray
 - Loctite 384 adhesive
 - Loctite 7387 activator
 - Loctite 242 threadlocker

Detailed information of handling of Cree LEDs can be found on www.cree.com.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.

TriplePowerEmitter XP

Assembly and Safety Information

- The photobiological safety of the LED modules must be classified into risk groups in accordance with EN 62471:2008.
 - general lighting
exempt group: WU-M-422
 - other applications
risk group 2: WU-M-422
- Use of standard VS optics does not affect the need to classify LED modules into the above mentioned risk groups.

Applied Standards

EN 62031
LED modules for general lighting – Safety specifications

EN 62471
Photobiological safety of lamps and lamp systems

Product Guarantee

- 5 years
- The conditions for the Product Guarantee of the Vossloh-Schwabe Group shall apply as published on our homepage (www.vossloh-schwabe.com). We will be happy to send you these conditions upon request.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.